

-30°C ÷ +300°C



				<b>1</b> daN	<b>2</b> daN	<b>daN</b>	Glijdlager			
								COD.		
80	35	12	39	250	125	150	0.18	672201*		
100	35	15	44	300	130	200	0.29	672202*		
125	35	15	44	400	180	300	0.43	672203*		
150	50	20	58	500	190	300	0.90	672104*		
200	50	20	58	700	240	500	1.68	672106*		

**1** statisch draagvermogen daN (kg)

**2** rolweerstand daN

**daN** dynamisch draagvermogen daN (kg)

\* = RoHS compliant











								NLX		NLX		
									COD.		COD.	
80	35	107	100x85	80x60	9	39	150	0.71	677701*	0.40	678701*	
100	35	128	100x85	80x60	9	35	200	0.79	677702*	0.52	678702*	
125	35	156	100x85	80x60	9	37	220	0.92	677713*	0.80	678713*	
150	50	194	140x110	105x80	11	56	300	2.21	677704*	1.77	678704*	
200	50	240	140x110	105x80	11	56	300	3.06	677706*	2.60	678706*	



						NLX			
							COD.		
80	35	107	73	12	39	150	0.62	676701*	
100	35	128	73	12	35	200	0.72	676702*	
125	35	156	73	12	37	220	1.05	676703*	



		PX		PX			
			COD.		COD.		
<b>150</b> <b>50</b> 200   140x110   105x80   11	70 <b>300</b>						
<b>200</b> <b>50</b> 250   140x110   105x80   11	70 <b>500</b>	