


WIELEN VAN GLASVEZEL VERSTERKT POLYAMIDE
STANDAARD (NL) GAFFELS



68FV



-30°C ÷ +30 °C



				1 daN			2 daN			kogellagers		rvs kogellagers			
100		30		12		45		250		400		250			
125		30		12		45		350		500		350			
100	30	12	45	250	400	250	0.27	683502*	0.27	683602*					
125	30	12	45	350	500	350	0.33	683503*	0.33	683603*					

1 statisch draagvermogen daN (kg) 2 rolweerstand daN daN dynamisch draagvermogen daN (kg) * = RoHS compliant



















								NL		NL					
							daN		COD.		COD.				
100	30	128	100x85	80x60	9	35	220	0.74	684882*	0.63	685182*				
125	30	156	100x85	80x60	9	37	220	0.83	684883*	0.72	685183*				














							NL					
						daN		COD.				
100	35	128	73	12	35	220	0.69	688082*				
125	45	156	73	12	37	220	0.78	688083*				



								NLX 		NLX 	
									COD.		COD.
100	30	128	100x85	80x60	9	35	220	0.74	 684682*	0.63	 685682*
125	30	156	100x85	80x60	9	37	220	0.83	 684683*	0.72	 685683*



							NLX 	
								COD.
100	35	128	73	12	35	220	0.69	 685982*
125	45	156	73	12	37	220	0.78	 685983*