



- | | |
|---------------------------|------------------------|
| 1. ZRS afdichtingsring | 5. Buitenring |
| 2. Ondersteuning drukring | 6. Cilinderrollen |
| 3. Axiaal deel | 7. Binnenring |
| 4. Draaipunt | 8. ZRS afdichtingsring |

Technische data Verstelbare combinatielagers -I- profiel

Type	d	T	D	H	h	B	A	S	r	C kN	Co kN	Ca kN	Coa kN	D op bestelling	Voor profiel
400-0075 (4.0075)	40	53	77,7	45	34	23	7	21	4	58,4	100	28,2	35,8	78,1/78,5	3019
400-0077 (4.0077)	50	67	101,2	50,5	37,5	28	7	21	3	91	150	13,2	14,5	101,9	2912
400-0078 (4.0078)	55	71	107,7	58,5	44,5	31	8	33	5	92,5	157	25	28	108,2/108,5	3100
400-0259 (4.0259)	55	76	123,5	57	42	33	4,5	33	5	109,7	185,7	25	28	Op aanvraag	3353

- C = dynamisch draaggetal
 - Co = statisch draaggetal
 - Ca = axiaal dynamisch draaggetal

- Coa = axiaal statisch draaggetal
 - Lasbare astap uit staal St52 - toelerantie -0,05mm