



- 1. Ondersteuning
- 2. Axiaal deel
- 3. ZRS afdichtingsring
- 4. Ondersteuning drukring
- 5. Cilindrische rollen
- 6. Buitenring
- 7. Binnenring
- 8. ZRS afdichtingsring
- 9. Draaipunt

Technische data Verstelbare combinatielagers voor -U- profiel

Type	d	T	D	H	h	B	A	S	R	C kN	Co kN	Ca kN	Coa kN	D op bestelling	Voor profiel
400-0072 (4.0072)	30	42	62	43	33	20	5,5	16	3	39	65,2	5,8	6	62,5	2890
400-0073 (4.0073)	35	48	70,1	48	40	23	6,5	16	4	55,5	91,7	5,8	6	70,4/70,7	2867
400-0074 (4.0074)	40	53	77,7	51	39,5	23	7	21	4	58,4	100	13,2	14,5	78,1/78,5	2810
400-0076 (4.0076)	45	59	88,4	61	48	30	7	21	3	83,8	132,3	13,2	14,5	88,9	2811
400-0078 (4.0078)	60	71	107,7	73	59	31	8	33	5	94,2	160,7	25	28	108,2/108,5	2862
400-0079 (4.0079)	60	80	123	75,8	59,5	37	8	33	5	128	226,8	25	28	Op aanvraag	2891
400-0080 (4.0080)	60	103	149	89	69	45	15	50	5	172,3	325,9	83	130	Op aanvraag	2757

C = dynamisch draaggetal
Co = statisch draaggetal
Ca = axiaal dynamisch draaggetal

Coa = axiaal statisch draaggetal
Lasbare astap uit staal St52 - toelerantie -0,05mm